


EEPROM Serial-I2C 8K-bit 1K x 8 3.3V/5V 8-Pin SO N T/R

Manufacturer:	STMicroelectronics, Inc
Package/Case:	SOP8
Product Type:	Memory
RoHS:	RoHS Compliant/Lead free 
Lifecycle:	NRND



Images are for reference only

[Inquiry](#)

General Description

The M24C08 is an 8-Kbit I2C-compatible EEPROM (Electrically Erasable PROgrammable Memory) organized as 1 K × 8 bits.

The M24C08-W can be accessed with a supply voltage from 2.5 V to 5.5 V, the M24C08-R can be accessed with a supply voltage from 1.8 V to 5.5 V, and the M24C08-F can be accessed either with a supply voltage from 1.7 V to 5.5 V (over the full temperature range) or with an extended supply voltage from 1.6 V to 1.7 V. All these devices operate with a clock frequency of 400 kHz.

Key Features

Compatible with I2C bus modes:

400kHz

100kHz

Memory array:

8Kbit (1Kbyte) of EEPROM

Page size: 16byte

Single supply voltage:

M24C08-W: 2.5V to 5.5V

M24C08-R: 1.8V to 5.5V

M24C08-F: 1.7V to 5.5V (full temperature range) and 1.6V to 1.7V (limited temperature range)

Write:

Byte Write within 5ms

Page Write within 5ms

Operating temperature range:

from -40°C up to +85°C

Random and sequential Read modes



Recommended For You

M24C08-RMN6TP

STMicroelectronics, Inc
SOP8

M27C64A-15F1

STMicroelectronics, Inc
DIP

M24C08-WDW6TP

STMicroelectronics, Inc
TSSOP8

M24C02-RMN6P

STMicroelectronics, Inc
SOP-8

M27C1001-10F1

STMicroelectronics, Inc
CDIP32

M27C1001-12F6

STMicroelectronics, Inc
DIP

M27C64A-20F1

STMicroelectronics, Inc
DIP

M27C512-15F1

STMicroelectronics, Inc
CDIP

M24C02-RMN6TP

STMicroelectronics, Inc
SOP-8

M27C1001-70F1

STMicroelectronics, Inc
DIP

M24C32-WMN6TP

STMicroelectronics, Inc
SOP-8

M27C512-90B6

STMicroelectronics, Inc
DIP28

M27C4001-90C6

STMicroelectronics, Inc
PLCC-32

M27C1001-70C1

STMicroelectronics, Inc
PLCC32

M24256-DFCS6TP/K

STMicroelectronics, Inc
WLCSP-8