

LCD Display LCD Driver 3.3V/5V 16-Pin WQFN EP T/R

Manufacturer: [Texas Instruments, Inc](#)**Package/Case:** WQFN16**Product Type:** Optoelectronics**RoHS:** RoHS Compliant/Lead free **Lifecycle:** Active

Images are for reference only

[Inquiry](#)**General Description**

The TPS65135 device is a high-efficiency split-rail power supply. Thanks to its single-inductor, multiple-output (SIMO) topology, the converter uses very few external components. The device operates with a buck-boost topology and generates positive and negative output voltages above or below the input supply voltage. The SIMO topology achieves excellent line and load regulation, which is necessary, for example, to avoid disturbance of a mobile phone display as a result of input voltage variations that occur during transmit periods in mobile communication systems. The device can also be used as a general-purpose split-rail supply as long as the output current mismatch between the rails is less than 50%.

Key Features

Single-Inductor, Multiple-Output Topology

2.5-V to 5.5-V Input Voltage Range

750-mW Output Power at $V_I = 2.9\text{ V}$

Positive Output Voltages Up to 6 V

Negative Output Voltage Down to -7 V

1% Output Voltage Accuracy

Up to 50% Output Current Mismatch Allowed

Excellent Line Regulation

Advanced Power-Save Mode for Light-Load Efficiency

Low-Noise Operation

Out-of-Audio Mode



Short-Circuit Protection

Thermal Shutdown

3-mm × 3-mm Thin QFN Package

Description

The TPS65135 device is a high-efficiency split-rail power supply. Thanks to its single-inductor, multiple-output (SIMO) topology, the converter uses very few external components. The device operates with a buck-boost topology and generates positive and negative output voltages above or below the input supply voltage. The SIMO topology achieves excellent line and load regulation, which is necessary, for example, to avoid disturbance of a mobile phone display as a result of input voltage variations that occur during transmit periods in mobile communication systems. The device can also be used as a general-purpose split-rail supply as long as the output current mismatch between the rails is less than 50%.



Recommended For You

TPD3S014DBVR

Texas Instruments, Inc
SOT23-6

TPS2065CDBVR

Texas Instruments, Inc
SOT23-5

TPS2557DRBT

Texas Instruments, Inc
SON8

TPS2042BDR

Texas Instruments, Inc
SOP8

TPS2051BDR

Texas Instruments, Inc
SOP8

TPL7407LPWR

Texas Instruments, Inc
TSSOP16

TPS23753APWR

Texas Instruments, Inc
TSSOP14

TPS2116DRLR

Texas Instruments, Inc
SOT5X3-8

TPS259460ARPWR

Texas Instruments, Inc
VQFN-10

TPS23751PWPR

Texas Instruments, Inc
HTSSOP16

TPS65150QPWPRQ1

Texas Instruments, Inc
HTSSOP-24

TPS2410PWR

Texas Instruments, Inc
TSSOP-14

TPS22914BYFPR

Texas Instruments, Inc
DSBGA4

TPS2115ADRBR

Texas Instruments, Inc
VSON8

TPS2113ADRBR

Texas Instruments, Inc
SON8